

CX 8105

8M

Base Size	8 m
Total Weight - 25 cm Spacing	9.236 kg
Axle Weight (Empty) - 25 cm Spacing	5.720 kg
Hitch Weight (Empty)	760 kg
Working Width - 25 cm Spacing	8m
Number of Shanks - 25 cm Spacing	32
Frame Width - Main	1,524 m
- Wing	3,048 m
Transport Position - Width	3 m
- Height	4,3 m
- Length	11 m
Tank Capacity - Front Tank	2.110 l
- Rear Tank	1.585 l
- Third Tank - Optional	350 l
- Total	2 Tanks - 3695 l with 3rd Tank - 4045 l
Hydraulic Brakes	Optional
Tank Screens	Standard
Fan - Rated Speed	Up to 5000 r.p.m.
- Impeller Diameter	33 cm Diameter
- Noise Level	97,3 dB
Hydraulic Drive - blower drive piston type orbit motor 12cc (Closed Centre or Closed Centre Load Sensing systems required)	Blower and VRT - Minimum 80 l/min. Minimum 14.469 kPa (144 bar)
Metering - Ground Drive	Standard
- Variable Rate (VRT)	Optional
- GPS Compatible VRT	Optional
Tires - Cart	(2) 600/50-22.5 Alliance Tire
- Main Frame Rear Wheels	(2) 12.5L x 15 FI - Load Range F
- Wing Frame Front Castor Wheels (1 per wing)	(2) 12.5SL x 15 - 12 Ply Rating
- Wing Frame Rear Wheels (1 per wing)	(2) 12.5SL x 15 - 12 Ply Rating
Opener - Trip Out Force	Increases proportionally with Packing Force to a maximum of 272 kg
- Packing Force	Adjustable from 31,7 kg - 77,1 kg
- Packer Wheel	4.50" x 16" Semi Pneumatic Otico tire 4.80" x 16" Semi Pneumatic or Pneumatic 5.50" x 16" Semi Pneumatic Otico tire 5.50" x 16" Semi-Pneumatic 4.00" x 16" V Crown
- Ground Clearance	30,5 cm
Frame to Ground Clearance	81 cm
Frame Depth	238,8 cm center to center
Rank to Rank Spacing	119,4 cm center to center
Number of Ranks	3 Rows
Shank to Shank Spacing	75 cm on 25 cm Spacing
Weight Kit	Optional
Safety Lights	Standard
Safety Chain	Standard

Specifications are estimates and subject to change.

MORRIS